
DATE	DESCRIPTION OF CHANGE	REV
2021-01-23	XXXXXXXX	A
2021-08-03	Add a new model	B



ITEM	CLIENTS/PN	LENGTH	AWG	IMPEDANCE	IPT P/N
1	SLSP-8X-8X-0.5M	500±15	30	95Ω	待定
2	SLSP-8X-8X-1M	1000±20	30	95Ω	待定
3	SLSP-8X-8X-2M	2000±35	30	95Ω	待定

NO.	NAME	IPT NO.	DESCRIPTION	Q'TY	UNIT
⑨	WIRE		UL1571 30AWG	-	MM
⑧	LABEL		WHITE LABEL,L W=40*40	1	PCS
⑦	ACETATE TAPE		W=25MM ACETATE TAPE,BLACK	-	MM
⑥	WEAVE		W=12MM PLASTIC BRAID SLEEVE,PET,BLACK	-	MM
⑤	LATCH		SFF-8654 LATCH,SUS301 1/2H	2	PCS
④	Outer Shell		Black core material PBT	-	G
③	INNER MOLD		Internal Mould material	-	G
②	PCB		SFF-8654 8i STR PCB, Au 30" Min	2	PCS
①	CABLE		SAS CABLE:(30AWG*2C+2D)+HM 95Ω	-	MM

serial CABLES

TITLE	SAS SLIMSAS 8i PLUG TO 8i PLUG CABLE ASSEMBLY					SHEET	1/2
CUSTOMER		CUSTOMER P/N	SLSP-8X-8X-XX		DRAWING	lupeng	
DWG NO.	WIPT20210123001	UNIT	SCALE	REV	VIEW	CHECKED	lupeng
IPT P/N		mm	NONE	B		APPROVAL	


DATE	DESCRIPTION OF CHANGE	REV
2021-01-23	XXXXXXXX	A
2021-08-03	Add a new model	B

WIRING TABLE

P1		P2	
GND	A1	B1	GND
RX0+	A2	B2	TX0+
RX0−	A3	B3	TX0−
GND	A4	B4	GND
RX1+	A5	B5	TX1+
RX1−	A6	B6	TX1−
GND	A7	B7	GND
SB	A8	B8	SB
SB	A9	B9	SB
GND	A10	B10	GND
SB	A11	B11	SB
SB	A12	B12	SB
GND	A13	B13	GND
RX2+	A14	B14	TX2+
RX2−	A15	B15	TX2−
GND	A16	B16	GND
RX3+	A17	B17	TX3+
RX3−	A18	B18	TX3−
GND	A19	B19	GND
RX4+	A20	B20	TX4+
RX4−	A21	B21	TX4−
GND	A22	B22	GND
RX5+	A23	B23	TX5+
RX5−	A24	B24	TX5−
GND	A25	B25	GND
SB	A26	B26	SB
SB	A27	B27	SB
GND	A28	B28	GND
SB	A29	B29	SB
SB	A30	B30	SB
GND	A31	B31	GND
RX6+	A32	B32	TX6+
RX6+−	A33	B33	TX6−
GND	A34	B34	GND
RX7+	A35	B35	TX7+
RX7−	A36	B36	TX7−
GND	A37	B37	GND

P1		P2	
GND	B1	A1	GND
TX0+	B2	A2	RX0+
TX0−	B3	A3	RX0−
GND	B4	A4	GND
TX1+	B5	A5	RX1+
TX1−	B6	A6	RX1−
GND	B7	A7	GND
SB	B8	A8	SB
SB	B9	A9	SB
GND	B10	A10	GND
SB	B11	A11	SB
SB	B12	A12	SB
GND	B13	A13	GND
TX2+	B14	A14	RX2+
TX2−	B15	A15	RX2−
GND	B16	A16	GND
TX3+	B17	A17	RX3+
TX3−	B18	A18	RX3−
GND	B19	A19	GND
TX4+	B20	A20	RX4+
TX4−	B21	A21	RX4−
GND	B22	A22	GND
TX5+	B23	A23	RX5+
TX5−	B24	A24	RX5−
GND	B25	A25	GND
SB	B26	A26	SB
SB	B27	A27	SB
GND	B28	A28	GND
SB	B29	A29	SB
SB	B30	A30	SB
GND	B31	A31	GND
TX6+	B32	A32	RX6+
TX6−	B33	A33	RX6+−
GND	B34	A34	GND
TX7+	B35	A35	RX7+
TX7−	B36	A36	RX7−
GND	B37	A37	GND

LABEL INFORMATION



TEST CONDITIONS:

1.100% OPEN & SHORT & MISS-WIRING & INTERMITTENCE TEST
2.CONDUCTIVE RESISTANCE: 3Ω MAX
3.INSULATION RESISTANCE：10 MΩ
4.HI-POT TEST： 300VDC FOR 10ms.
5.THIS PRODUCT MEETS SAS 4.0

this drawing Is the property of Serial Cables and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other han Serial Cables without its prior consent,and that no right is granted to disclose or use any Information in this drawing

TITLE	SAS SLIMSAS 8i PLUG TO 8i PLUG CABLE ASSEMBLY					SHEET	2/2
CUSTOMER		CUSTOMER P/N		SLSP-8X-8X-XX		DRAWING	lupeng
DWG NO.	WIPT20210123001	UNIT	SCALE	REV	VIEW	CHECKED	lupeng
IPT P/N		mm	NONE	B		APPROVAL	